Sioux - Pneumatic

TM Series Torque Multipliers

Features:

- Lightweight Titanium Gear Case Offers 30% weight savings than standard steel gear casing
- Two Speed Gear Shift More versatility and higher torque range
- High Quality Gears For longer operating life expectancy between repairs
- Ergo Over Molded Grip more comfort on the hand
- Integrated swivel joint between drive and gear case -Insures reaction-free operation over the entire bolting cycle
- Fine pressure Control for torque pre-selection Ultimate control
- No lateral or impact forces transmitted from tool to user No sparks
- from

	Torque						Speed				Noise
Model	Drive Size		Gear 1		Gear 2		Gear 1	Gear 2	Weight		Level
Number	in.	mm	ft lb	Nm	ft lb	Nm	rpm	rpm	lb	kg	dB(A)
TM50AP-0775	3/4	19	45-188	61-255	125-580	169-786	69	12	10.7	4.9	84
TM50AP-1075	1	25	59-295	80-400	220-900	298-1220	30	8	13	5.9	84
TM50AP-15100	1	25	40-370	54-502	150-1300	203-1763	25	7	15.6	7.1	84
TM50AP-25100	1	25	110-600	149-813	340-2100	461-2847	9.4	2.6	22.4	10.1	84
TM50AP-45150	1-1/2	38	160-1100	217-1491	500-3500	678-4785	6	1.7	23.1	10.5	84
TM50AP-60150	1-1/2	38	220-1600	298-2169	650-5000	881-6779	5.3	1.5	36.3	16.5	84

Filter-Regulator-Lubricator Kit

Model: FRLK1660

Weight: 17lb

Includes 10 ft. 3/8" Hose, Stand, Filter, Regulator, Lubricator, Nuts and Bolts for mounting, and Pressure Gauge.

The FRLK1660 unit shown below is highly recommended, as the FRLK1660 is used to regulate the air pressure and properly lubricate the air motor for ultimate life between service. The chart is an example of what's included in each tool's operation's manual. Air pressure regulates and controls torque output. All TM series tools must be used with and FRL and it's strongly advised not to exceed the maximum amount of air pressure.

General:

Air Inlet Size: 1/4" NPT (Please use high flow fittings only) Recommended Hose Size: 3/8" (10 mm) (1450 series) Performance rated @ various air pressures as specified in operations manual Standard Equipment: Parts list, Safety and Instruction manual Reaction arm

Metal carrying case



WARNING • Read and follow all safety and operating instructions. • Face ane eye protection must be worn while TM50AP-4515