BID SPECIFICATION



Snap-on® MODIS™ Edge Integrated Diagnostic System

PRODUCT FEATURES

- Integrated multifunction diagnostic & information system
- Upgradeable software
- 2-channel lab scope with Guided Component Tests
- Digital & graphing multimeter
- · Color graphing scan tool
- Domestic and Asian Fast-Track® Troubleshooter
- Data manager function
- Keyless scan adapter for OBD-II compliant vehicles
- Steady-charge battery technology charges directly from vehicle via data cable

DISPLAY

 8" Color, 800 x 480 resolution, resistive touch panel, backlit LCD

SYSTEM & USER INTERFACE

- SMX embedded dedicated operating system
- Boots in 5 Seconds
- Touchscreen navigation

STANDARD ACCESSORIES

- Keyless OBD-II vehicle communication interface cable with flashlight feature for 1996-newer vehicles
- Two shielded, color-coded scope leads
- Two insulated test probes
- Three insulated test clips
- 110VAC power adapter
- Removable Lithium-ion battery pack
- USB cable
- Quick-start guide and info pack
- ShopStream connect PC interface software (Download)

SCAN TOOL SPECIFICATIONS

- Instant ID (Auto ID using Mode 9 VIN)
- SureTrack Expert Information
- Oil Specs and Reset data
- Snap-on vehicle communication and Fast-Track Troubleshooter software included
- Reads & clears OBD-II and OEM-specific trouble codes
- Displays complete trouble code descriptions
- Displays from one to four live data parameters (PIDs) simultaneously in graphing mode
- Displays eight live data parameters (PIDs) simultaneously in text mode

- Adjustable sweep; Min/Max capture in graphing mode
- Includes functional tests, bi-directional controls and reset/relearns
- Save screen captures and scanner movies
- Saves and stores previous vehicle identification
- Software coverage for 1980-newer US Domestic, 1983newer Asian Import and optional coverage for 1992-newer European vehicles
- Optional European vehicle software with enhanced coverage for Alfa Romeo, Audi, BMW, FIAT, Jaguar, Land Rover, MINI, Mercedes, Porsche, SMART, Volvo and VW

GLOBAL OBD-II VEHICLE COMMUNICATION SOFTWARE

- Communicates with 1995 and newer EOBD/OBD-II compatible vehicles
- Automatically establishes communication with the appropriate vehicle protocol

Covers 10 Modes of OBD-II

- Mode 1: graphs or displays current data
- Mode 2: retrieves freeze frame data
- Mode 3: monitors diagnostic trouble codes
- Mode 4: clears emissions related data
- Mode 5: oxygen sensor monitoring
- Mode 6: non-continuously monitored systems
- Mode 7: diagnostic trouble codes detected during last drive
- Mode 8: bi-directional controls (where available)
- Mode 9: displays important vehicle information
- Mode 10: permanent codes

GM VEHICLE COMMUNICATION SOFTWARE 1980 - 2016

- Enhanced OBD-I, OBD-II & Generic OBD-II modes
- Engine/Powertrain, Transmission, ABS, Airbag, Body, Instrument Panel, Vehicle Theft Deterrent, Tire Pressure Monitor, Transfer Case, Trailer Brake Control, HVAC, Suspension, Keyless entry, Climate control Diagnostics, Code Scan, Clear All Codes, Seats, Parking Brake, Steering Angle, Auto-ID
- Front View Camera
- Radio/HVAC
- Headlamp Modules
- Auxiliary Body Controls
- Air Suspension
- Active Grill Air Shutter Module
- Object Detection
- Telematics
- Seat Modules
- Rollover Sensor for Safety Systems
- 6.6L Crankshaft Position (CKP) Sensor Test
- Passenger Presence
- Diesel Power Balance Test
- Vehicle Theft Deterrent Codes, Data & Indicator Status
- Radio Systems Codes, Data & Test Including VIN Write
- HVAC Actuator & Recalibration
- 6.6L Turbo Tests
- Theft Deterrent, Keyless Entry and Remote Function Actuation
- ABS & Air Bag GM symptom codes
- Brake Pedal Pressure (BPP) Relearn

- BID SPECIFICATION -

- Engine Bi-Directional Testing, incl. EVAP Monitor Test and EVAP System Testing, Output Controls, Injector Balance, ICB, IAC, EGR, Crank Position Relearn
- Particulate Filter Replacement & Fuel Filter Life Reset Function – Diesel engines where applicable
- Transmission Bi-Directional Testing, incl. Solenoid Tests, Trans Shifting and Adaptive Resets
- ABS Diagnostics and Brake Bleeding
- Dash and Rear Integration Modules
- 2004 and newer Key Fob Programming

FORD VEHICLE COMMUNICATION SOFTWARE 1981 - 2015

- Enhanced OBD-I, OBD-II & Generic OBD-II modes
- Engine, Transmission, ABS, Airbag, Occupant Classification, Body/GEM, Instrument Panel, Anti-Theft, Transfer Case, GEM, 4x4 Module, Tire Pressure Monitor, Door modules, Driver's Seat, Sliding Door, Liftgate Trunk, Power Running Boards, Lighting Control, Auto Temp Control/HVAC, Navigation, Parking Aid, Electric Power Steering, Battery Control Diagnostics
- Injector Balance and Relative Compression Engine Tests
- Injector Quantity Adjustment and Injector Buzz Diesel Engine Test
- Clutch Tests and Relearn for Auto-Shifting Manual Transmissions
- Airbag Sub-Codes
- PATS Key Programming (CAN Vehicles)
- Battery Monitor
- Crankshaft Position (CKP) Relearn
- Engine Functional Tests
- EVAP
- Code Scan and Clear All Codes
- CAN UDS Auto-ID
- OEM Sub codes
- Diesel Particulate Filter (DPF) tests and Manual Regeneration
- 6.7L Functional Tests
- 6.7L alow plug test
- Ford/Lincoln Air Suspension Re-calibration
- Engine Bi-Directional Testing, incl. EEC V engine controls, EVAP System Testing, Cold Soak Test, 7.3 Powerstroke Cylinder Contribution
- EGR functional test & Injector power balance 6.0 diesels
- Vane Turbo Functional Test 6.0 diesel
- Cylinder Contribution test includes non-CAN, CAN and UDS Vehicles, where applicable
- Transmission Bi-Directional Testing, incl. Transmission Bench and Drive Tests, Gear Command, Adaptive Learning, Trans Table Resets
- ABS Diagnostics, Brake Bleeding and Pump Motor Test, incl. Bosch, Teves, and Kelsey-Hayes
- Air suspension codes, data, functional test

CHRYSLER VEHICLE COMM SOFTWARE 1983 – 2015

- Enhanced OBD-I, OBD-II & Generic OBD-II modes
- Engine, Transmission, ABS, Airbag, Body, Occupant Classification Module, TPMS, Electronic shifter, HVAC, Steering Angle Sensor, ESP, Door Modules, Park Assist, Central Gateway, Instrument Panel, Transfer Case Diagnostics, Code Scan
- Dodge/Ram® 4500/5500 series truck coverage
- · Electronic limited slip differential

- Adaptive front lighting system
- TPMS threshold adjustment function
- Active Dampening
- Blind Spot Module
- Adaptive Cruise Control
- Air Suspension
- BCM Configuration
- Sub Codes
- 6.7L Transmission Quick Learn
- Pinion Factor
- Diesel Exhaust Fluid (DEF) Tests
- HVAC Systems
- Engine Misfire Detection
- Diesel Cylinder Performance Test
- DPF Stationary De-Soot
- NAG Transmission Resets & Initialization
- Engine Bi-Directional Testing, incl. Actuator Tests, Forced EVAP Monitor Test, Set RPM/IAC Test, Purge Vapors Test, EGR System Test, ETC Throttle Follower Test, Misfire Counters, Generator Field, PCM VIN Programming
- Particulate Filter Replacement & Fuel Filter Life Reset Function – Diesel engines where applicable
- Transmission Bi-Directional Testing, incl. EMCC Reset, Quick Learn, Quick learn CAN, Battery Disconnect
- ABS brake bleed incl. Kelsey-Hayes, Teves, Bendix
- Body ATM Tests, incl. Door Locks, Lights, Chimes, Horn, Wipers, Sunroof and Overhead Module
- TPMS including sensor ID function

ASIAN VEHICLE COMM SOFTWARE 1983 - 2016

- Enhanced OBD-I, OBD-II & Generic OBD-II modes
- In-depth Engine (including Hybrid), Transmission, Airbag & ABS, HVAC, Instrument, TPMS, Cruise Control, Code Scan, Clear All Codes, Power Steering coverage for popular Asian Import vehicle makes:

Acura, Daihatsu, Honda, Hyundai, Infiniti, Isuzu, Kia, Lexus, Mazda, Mitsubishi, Nissan, Scion, Subaru, Suzuki, Toyota

- Honda/Acura® integrated motor assist (IMA) system coverage
- Honda Engine Control Module (ECM) Replacement Function
- Honda Transmission Control Module (TCM) Replacement Function
- Hvundai transmission adaptations
- Hyundai Body Control Module (BCM)
- Hyundai/Kia electronic power steering functions
- Hyundai/Kia/Mazda Occupant Classification Module (OCM)
- Mazda Engine and ABS Functional Tests
- Mitsubishi Vehicle Coding
- Nissan/Infiniti Intelligent Key System
- Hyundai/Kia Advanced Safety Systems (Smart Cruise Control, Lane Departure Warning, Blind Spot Detection Systems)
- Mitsubishi Timing Chain Maintenance Functions
- Toyota/Lexus Park Assist System
- Toyota Multiple Freeze Frame
- Mazda Sub Codes
- Suzuki Code Scan
- Nissan Electronic Power Steering (EPS)
- Nissan/Infiniti® body control module (BCM) configuration

- BID SPECIFICATION -

- Honda Adaptive Cruise, Collision and Lane Module, Blind Spot Info
- Hyundai/Kia Electronic Park Brake
- Toyota Push Start Button
- Toyota Electronic Activated Control (EAC) Mounts
- Toyota/Mazda Auto-ID
- Suzuki 4WD and Power Steering
- Toyota/Lexus/Scion Transmission, Park Brake and Main Body
- Nissan/Infiniti HVAC Codes, Data & Test
- Suzuki HVAC Codes, Data & Test
- Mazda EVAP Test
- Hyundai & Kia Power Intelligent Control System
- Honda Civic and Acura Hybrid Brake
- Suzuki TPMS Systems
- Toyota Air Injection Test
- Mazda ABS Function Tests
- Lexus Air Suspension
- Toyota VIN Writing, Immobilizer System, Engine Memory Reset and Door/Mirror Modules
- Honda & Acura Occupant Detection
- Nissan Intelligent Cruise Control
- Hyundai, Kia and Mitsubishi PCM VIN Write
- Honda/Acura TPMS coverage including tire registration
- Honda active cruise control
- Honda VIN programming
- Hyundai and Kia power balance tests
- Subaru TPMS
- Nissan/Infiniti body control modules

DOMESTIC/ASIAN IMPORT DRIVEABILITY FAST-TRACK® TROUBLESHOOTER

General Motors, Ford, Chrysler/Jeep, Acura, Daihatsu, Honda, Hyundai, Infiniti, Isuzu, Kia, Lexus, Mazda, Mitsubishi, Nissan, Subaru, Suzuki, Toyota

- Domestic 1980 2015
- Asian Imports 1983 2015
- Troubleshooter procedures that verify a repair is completed and fixed properly
- Exclusive experience-based information
- Over 6.8 Million VIN-specific Troubleshooter Tips
- Exclusive VIN-Specific troubleshooting and systems code tips, no-code tips, no-start tips, drivability symptoms and frequent component failures
- Enhanced OBD-II Fast-Track data scan tips reflect manufacturer-specific enhanced data stream capabilities
- Component locators
- Service procedures and specifications
- Code set specifications
- Fast-Track wiring diagrams, VIN-specific service bulletins and procedures
- Enhanced diesel symptom tips
- Enhanced functional test descriptions
- Firing orders and cylinder locations

DOMESTIC/ASIAN IMPORT TRANSMISSION FAST-TRACK TROUBLESHOOTER

- Domestic 1981 through 2015 model year
- Asian import 1983 2015
- Electronic Controlled Transmission/transaxle coverage
- Technical service bulletins

- Enhanced Fast-Track data scan tips
- Transmission functional test insight
- Hundreds of transmission wiring diagrams

DOMESTIC/ASIAN IMPORT ABS, BODY, AIRBAG FAST-TRACK TROUBLESHOOTER

- Solutions for ABS-related codes through 2015 models
- Symptom-based tips for 2015 models and earlier
- 24 vehicle makes supported
- Additional reference material and service bulletins
- Electronic steering & alignment functions

FAST-TRACK TROUBLESHOOTER REFERENCE DATABASE

- Codes in the tool provide user reference to lookup related information at <u>www.askatech.com</u> for 24 vehicle makes
- OEM-sourced information, including diagnostic reference information from TSBs, service manuals, test procedures, vehicle specifications, schematics, wiring diagrams, and more
- Coverage for drivability, transmissions and brake systems

NOTE: Scan tool coverage varies by model. Information current as of 10/10/2016. Subject to change without notice.

LAB SCOPE SPECIFICATIONS

Two-Trace Scope: Captures and displays up to two waveforms.

Sample rate of 6 million samples per second on one channel (at 50 us sweep).

Sample rate of 3 million samples per second on two channels (at 100 us sweep).

Note: Also see SCOPE/METER SYSTEM SPECIFICATIONS at end of this document

- Displays digital readout along with each waveform
- Color-coded waveform for each channel
- Manual & automatic (GCT) configuration
- AC Coupling
- Invert
- Peak Detect

DIGITAL & GRAPHING MULTIMETER SPECIFICATIONS

- Auto scaling, high-impedance multimeter measurement system
- Digital and graphing display of results
- Pinpoint measurement of:
- Volts DC, Volts DC Average, Volts AC RMS, Diode/Continuity, Ohms, Frequency, Pulse-width, Injector pulse width, Duty cycle, Low Amps, MC Dwell, Vacuum, Pressure, Temperature, Ohms
- o Interface for optional pressure/vacuum transducers
- o Continuity tester with audible beep

FAST-TRACK GUIDED COMPONENT TESTS

- Built-in Guided Component Test software
 - Coverage for over 40 domestic, Asian and European makes; 1979-newer
 - o Guided test procedures for over one million components

- BID SPECIFICATION -

- Test coverage for sensors, solenoids, injectors, charging/starting systems, ignition, motors, pumps, ABS and more
- o Automatic meter setup
- o Component description and operation
- o Connector diagrams and connection tips
- o Known good test values
- o Reference Waveforms
- · Onboard training and product information

POWER/WEIGHT/DIMENSIONS

- Battery: Lithium-ion battery pack included
- 3 Hour run time (50% Brightness)
- Dimensions: 11.0"W x 6.3"H x 1.6"D
- Weight: 2.65 lbs

OPTIONAL ACCESSORIES – SCAN TOOL

- OBD-I Adapter Master Kit EAK0301B10A
- European Vehicle Keys and Adapters Kit EAK0301B07C (1992 newer BMW, 1992 newer VW/Audi, 1992 newer Mercedes-Benz, 2000 newer Jaguar, 2000 newer Land Rover, 1996 newer MINI, 2000 newer Volvo, 2005 newer SMART)
- Adapter for Kia ABS & Airbag EAA0355L92A
- Scanner demo board EESX306ASC

OPTIONAL ACCESSORIES - IGNITION ADAPTERS

- Secondary Coil Adapter Lead EETA309A05A
- EETM306A02 Secondary Ignition clip-on Wire Adapter
- EETM306A03 COP-1 Ford
- EETM306A04 COP-2 Chrysler
- EETM306A05 CIC-2 Honda, Toyota
- EETM306A06 CIC-1 GM
- EETM306A07 COP-3 Audi, VW
- EETM306A08 COP-4 Acura/Honda, Isuzu
- EETM306A09 COP-5 Volvo/BMW
- EETM306A10 COP-6 Mercedes
- EETM306A11 COP-7 Mercedes Dual
- EETM306A12 COP-8 BMW
- EETM306A13 COP-9 Lexus
- EETM306A14 COP-11 Audi, BMW, Chrysler, Jeep, Lexus, Mercedes, Saab, Toyota, Volvo, VW

OPTIONAL ACCESSORIES - LAB SCOPE/METER

- Precision low amp current probe EETA308D
- 100 PSI Pressure/Vacuum transducer w/cable EEPV302AL
- 500 PSI Pressure transducer w/cable EEPV302AT
- 5000 PSI Pressure transducer w/cable EEPV302AH Note: Pressure transducers require optional pressure transducer adapter - EEMS324PSA
- Pressure transducer extension cable EAX0024B30A
- Scope demo board EESX306ASP

OPTIONAL ACCESSORIES – PROTECTION AND ORGANIZATION

- Foam drawer organizers for 3-series carts MODISEFOAM3
- Foam drawer organizers for 4-series carts MODISEFOAM4
- Screen protector 3-pack EAC0111L76A3

MODIS™ Edge EEMS341 - BID SPECIFICATION -

SCOPE/METER SYSTEM SPECIFICATIONS

MULTIMETER

Function	Range	Comments	
Channels	1 – 2	Common Ground	
Sample Rate	6.0 MSPS @ 50us sweep	Simultaneous	
	3.0 MSPS @ 100us sweep	Continuous per channel	
Bandwidth	DC – 3 MHz	3 db point @ 3 MHz	
Input Impedance	10 MΩ @ DC	- All channels	
	4 kΩ @ 3MHz	All Charmers	
V dc (Full Scale)	75 V maximum		
V ac (Full Scale) Peak to Peak Voltage	50 V maximum		

DIGITAL METER OHMS AND DIODE CONTINUITY TESTS

Function	Range	Comments		
Channels	1-2	Inputs between channels 1 (-) and 2 (+)		
Input Impedance	10 ΜΩ			
Glitch capture	Approximately 50 mS			
Ohms	400 Ω – 4 ΜΩ	Fixed scales or Auto Ranging		
Diode Test	2 V Scale			

GRAPHING MULTIMETER

Function	Range	Comments	
Input Channels	1 – 2		
Input Impedance	10 Megohm		
Volts (DC)	400 mV thru 400V*	Auto Ranging	
Frequency	5 Hz thru 50 KHz	Auto Threshold Setting	
Pulse Width	5 ms thru 2 s	Auto Threshold Setting	
Inj Pulse Width	5 ms thru 2 s		
MC Dwell (60)	20 - 40 - 60 degrees	Auto Threshold Setting	
MC Dwell (90)	30 - 60 - 90 degrees	Auto Threshold Setting	
Duty Cycle	20 - 40 - 60 - 80 - 100%	Auto Threshold Setting	
Low Amps (20)	1 - 2 - 5 - 10 – 20A	With EETA308D	
Low Amps (40)	10 – 20 - 40A	With EETA308D	
Low Amps (60)	10 - 20 - 40 - 60A	With EETA308D	
Vacuum	5 - 10 – 20 in Hg	Sensor specific	
100 psi Pressure	10 - 25 - 50 - 100 PSI	Sensor specific	
500 psi Pressure	50 - 100 - 250 - 500 PSI	Sensor specific	
5000 psi Pressure	500 - 1000 - 2500 - 5000 PSI	Sensor specific	

^{*} See Safety Warnings in MODIS Edge user manual

MODIS™ Edge EEMS341 - BID SPECIFICATION -

LAB SCOPE

Function	Range	Comments	
Channels	1 – 2	Common Ground	
Bandwidth	DC - 3 MHz	3 db point @ 3 MHz	
Input Impedance	10 MΩ @ DC	All channels	
Input Impedance ———	4 kΩ @ 3MHz	All channels	
	400 Volts		
	200 Volts		
	100 Volts		
VDC (full scale)	50 Volts		
Do not test greater than 75Vdc	20 Volts		
	10 Volts		
VAC (full scale)	5 Volt		
Peak to Peak Voltage	2 Volt		
Do not test greater than 50Vac (rms)	1 Volt		
	500 millivolt		
	200 millivolt		
	100 millivolt		
Secondary Ignition	1 – 50 KV	Channels 1 and 2	

LAB SCOPE SPECIFICATIONS BY SWEEP RATE

Sweep	Channels	Data points per screen	Buffer storage/Ch	Max # Screens	Total time ¹	Sample rate ²	Peak Detect ³
50 μs	Ch 1	300	524,288	1747	87.8 ms	6.0 MHz	N
100 μs	Ch 1,2	300	261,120	870	87.0 ms	3.0 MHz	N
200 μs	Ch 1,2	300	262,080	873	174.6 ms	1.5 MHz	N
500 μs	Ch 1,2	500	262,140	524	262 ms	1.0 MHz	N
1 ms	Ch 1,2	500	262,080	524	524 ms	500 KHz	Υ
2 ms	Ch 1,2	500	262,080	524	1.0 S	250 KHZ	Y
5 ms	Ch 1,2	500	262,080	524	2.6 S	100 KHz	Υ
10 ms	Ch 1,2	500	262,080	524	5.2 S	50 KHz	Υ
20 ms	Ch 1,2	500	262,140	524	10.4 S	25 KHz	Υ
50 ms	Ch 1,2	500	262,140	524	26.2 S	10 KHz	Y
100 ms	Ch 1,2	500	262,140	524	52.4 S	5 KHz	Υ
200 ms	Ch 1,2	500	262,140	524	1.7 M	2.5 KHz	Υ
500 ms	Ch 1,2	500	262,140	524	4.4 M	1.0 KHz	Υ
1 s	Ch 1,2	500	262,140	524	8.7 M	500 Hz	Υ
2 s	Ch 1,2	500	262,140	524	17.5 M	250 Hz	Y
5 s	Ch 1,2	500	262,140	524	43.6 M	100 Hz	Y
10 s	Ch 1,2	500	262,140	524	87.3 M	50 Hz	Y
20 s	Ch 1,2	500	262,140	524	174.6 M	25 Hz	Υ

^{*} See Safety Warnings in MODIS Edge user manual

^{1 -} Total time is equal to the sweep times the number of screens.

^{2 -} Actual sample rate for sweeps 50-200 µs. Effective sample rate for sweeps 500 µs and longer. The effective sample rate is based on the number of sample points stored to the data buffer memory over the selected time sweep. On all sweeps 500 µs and longer, the ADC samples at 1.5 MHz per channel regardless of sweep. The number of sample points is greater than the number of points needed to complete a screen. Only enough points to complete a screen are selected to be stored to the data buffer. This results in the effective sample rate being lower than the actual sample rate of 1.5MHz.

^{3 -} When Peak Detect is on, all samples are evaluated. The points stored to the buffer are intelligently selected to capture fast events that might be missed at slower effective sample rates. Peak Detect will capture fast changes at an effective sample rate of 1.5MHz.