



1/4 in. Recessed Square Drive Micro-Cordless Screwdriver with Interchangeable Shanks and Bits

CTS661SK

Features and Benefits

- 100 in. lbs. (11 N·m) of Torque Output
- Patent-pending Oversized forward/reverse cushion toggle style variable speed trigger—one-hand operation to toggle quickly from forward to reverse
- Twin-beam headlights illuminate work area
- Built-in brake stops the tool from throwing sockets and fasteners
- Quick 30 minute battery charge for less down time
- Over current protection protects the electronics
- Under voltage protection will not overdraw the battery
- Built-in gauge lets you know the state of the battery charge
- Screened motor keeps debris from entering critical components
- Cushion grip handle provides positive tool control with less fatigue
- Over and under temperature protection keeps tool operating at peak efficiency
- Glass-filled nylon housing for durability



CE – DE, ES, FR, IT, GB, NL, JP



Country of Origin – China





CTS661SK

Specs

- 100 in. lbs. (11 N·m) of torque output
- 275 in. lbs. Spindle Lock
- 400 rotations per minute (RPM)
- Weight 1.8 lbs. with battery (0.8 kg)
- Length 6.3 in. (160 mm)
- Height 6.9 in. (177 mm)
- Width 1.9 in. (50 mm)
- Voltage 7.2 VDC
- Hex Drive 1/4 in.
- Built-in LED light
- 9-position Clutch
- Sound Pressure Level 88.4 dB
- Vibration Level 3.79 m/s²

CTS661SK Set Components

- CTS661S – 7.2 Volt Lithium Screwdriver
- CTB6172 – 7.2 Volt Lithium Battery (2)
- CTC772 – 3.0 Amp Lithium Charger
- PB171 – Soft Sided Case
- GMB3041 – 1 in. long adaptor, 1/4 in. hex to 1/4 in. square
- GMB3042 – 2 in. long adaptor, 1/4 in. hex to 1/4 in. square

BITS — BELOW:

- BTS2 - #2 Scrulox
- SDM221C - #1 Phillips
- SDM222CZ - #2 Phillips, limited clearance
- SDM222IRB - #2 Phillips ACR Installer/Remover
- SDM223C - #3 Phillips
- SDM211B – Flat tip, 0.033 in. x 0.187 in.
- SDM213B – Flat tip, 0.040 in. x 0.250 in.
- SDM2708D – 1/8 in. Hex
- SDM2709D – 9/64 in. Hex
- SDM2710D – 5/32 in. Hex
- SDM2712D – 3/16 in. Hex
- SDM2714D – 7/32 in. Hex
- SDM2716D – 1/4 in. Hex (continued on page 3)



CTS661SK

- SDMM2703B – 3mm
- SDMM2704C - 4mm
- SDMM2705C - 5mm
- SDMM2706C - 6mm
- SDMM2708B - 8mm
- SDMT10D – Torx T10
- SDMT15D - Torx T15
- SDMT20D - Torx T20
- SDMT25D - Torx T25
- SDMT30D - Torx T30

SHANKS — BELOW

- SGDMRC1-10 – Shank, 1 in. long
- SGDMRC4-40 – Shank, 4 in. long

RATCHETING HANDLE — BELOW

- SGDMRC4A – 6 in. long, Soft Grip, Standard, Red

Related Items

- CT625 – 1/4 in. Cordless Impact Kit
- CT625DB – 1/4 in. Cordless Impact (tool only)
- CT661 – 3/8 in. Cordless Impact Kit
- CT661QC – 1/4 in. Cordless Impact Driver
- CTS661 – 1/4 in. Cordless Screwdriver
- CTL761 – Lithium Work Light
- CT661DB – 3/8 in. Cordless Impact (tool only)
- CT661QCDB – 1/4 in. Cordless Impact Driver (tool only)
- CTS5661DB – 1/4 in. Cordless Screwdriver (tool only)



WARNING



•Use only impact sockets and accessories.



•Wear safety goggles. (User and bystanders)



•Wear hearing protection. (User and bystanders)

• Read additional safety precautions on pages W1 to W4 in product catalog CAT1200